



zetaecotech
INNOVATIVE NURSERY TECHNOLOGIES

by **Electrozeta**

San Giorgio della Richinvelda (PN) - www.zetaecotech.it

ROOTSTOCKS CONVEYOR-BELT


HECO - BELT - SM: SEMI-AUTOMATIC UNLOADING SYSTEM

The Conveyor belt **HECO-BELT-SM** of the HECO Line by **Zetaecotech** has a **semi-automatic unloading system** and is equipped with lateral containing guides **to convey and align the rootstock branches previously processed** with the Disbudding Machine.

HECO-BELT-SM includes both a horizontal conveying system and an electro-pneumatic inclined automatic unloading device that aligns and deposits the processed shoots in a pre-arranged collector.

AVAILABLE LAYOUTS:


L06_SM
L09_SM
L12_SM



****SM= SEMI-AUTOMATIC UNLOADING SYSTEM**

DIMENSIONS:

****BELT MEASURES L06SM**



ELECTROZETA S.R.L.

Via Kechler, 12 - 33095 - San Giorgio della Richinvelda - (PN)


VAT Number 01125950939

Tel. 0427.96090 - e-mail: info@electrozeta.it - commerciale@electrozeta.it - PEC: electrozeta@legalmail.it - www.zetaecotech.it

ROOTSTOCKS CONVEYOR-BELT

Latest Update: 07/08/2023

MAIN TECHNICAL FEATURES:	HECO-BELT-L06SM	HECO-BELT-L09SM	HECO-BELT-L12SM	
PRICE FOR YOUR ATTENTION:				
TRANSPORT SYSTEM:	Green PVC carpet width 300 mm thickness 3 mm Nr. 1 gear motor with adjustable and controlled speed			
ALIGNMENT AND UNLOADING SYSTEM:	Nr. 1 unloading conveyor with manual adjustable tilting and rotation			
PROCESS CONTROL SYSTEM:	Electronic with operator controls on the belt			
BELT SPEED:	Steady until 5 km/h or adjustable from 3 to 6 km/h when inverter is present			
TOTAL ELECTRICAL POWER:	370 W			
ELECTRICAL POWER:	Three-phase 3P+N+T 400 V or single-phase 2P+T250 V 50/60 Hz			
PNEUMATIC POWER:	Compressed air 6 bar (86 psi)			
WORKING HEIGHT: (CARPET)	Adjustable from 800 to 1.050 mm			
BELT LENGHT:	6.000 mm	9.000 mm	12.000 mm	
TOTAL DIMENSIONS AND WEIGHT:	L 6.300 x W 800 x H 1.400 mm Weight: 150 Kg.	L 9.300 x W 800 x H 1.400 mm Weight: 180 Kg.	L 12.300 x W 800 x H 1.400 mm Weight: 210 Kg.	
SUPPORTING FRAME: BUILDING MATERIALS:	Profiled aluminium frame on pivoting wheels			
CARPET: BUILDING MATERIALS	Green PVC thickness 3 mm			
LATERAL GUIDES: BUILDING MATERIALS	Stainless steel sheet and partially galvanized			
ROOTSTOCK WORKABLE LENGHT:	6 - 7 meters	9 - 10 meters	12 - 13 meters	
STANDARD EQUIPMENT:	/			
OPTIONAL:	Specific collector			
TECHNICAL LEGISLATIONS:	Built in compliance with European Machinery Directive - EC Certified			



ELECTROZETA S.R.L.

Via Kechler,12 - 33095 - San Giorgio della Richinvelda - (PN)

VAT Number 01125950939

Tel. 0427.96090 - e-mail: info@electrozeta.it - commerciale@electrozeta.it - PEC: electrozeta@legalmail.it - www.zetaecotech.it